

AD-A085 871

ARMY MISSILE COMMAND REDSTONE ARSENAL AL DIRECTED E--ETC F/G 20/3
A SIMPLE METHOD FOR TREATING DIFFRACTIVE PROPAGATION FROM A LAS--ETC(U)
NOV 79 R W JONES, J C NIXON, J F PERKINS
DRSMI/RH-80-2

UNCLASSIFIED

NL

1 of 1
AD-A085 871



END
DATE
FILMED
8-80
DTIC

ADA 085871

(12) LEVEL II



TECHNICAL REPORT RH-80-2

**A SIMPLE METHOD FOR TREATING DIFFRACTIVE
PROPAGATION FROM A LASER WITH DIAGNOSTIC
OPTICS**

R. W. Jones

J. C. Nixon

J. F. Perkins

→ Directed Energy Directorate
US Army Missile Laboratory

19 November 1979



U.S. ARMY MISSILE COMMAND

Redstone Arsenal, Alabama 35809

Approved for public release; distribution unlimited.

DTIC
ELECTE
JUN 23 1980
S B D

DRG FILE COPY

FORM 1021, 1 JUL 79 PREVIOUS EDITION IS OBSOLETE

80 6 9 130

DISPOSITION INSTRUCTIONS

DESTROY THIS REPORT WHEN IT IS NO LONGER NEEDED. DO NOT
RETURN IT TO THE ORIGINATOR.

DISCLAIMER

THE FINDINGS IN THIS REPORT ARE NOT TO BE CONSTRUED AS AN
OFFICIAL DEPARTMENT OF THE ARMY POSITION UNLESS SO
DESIGNATED BY OTHER AUTHORIZED DOCUMENTS.

TRADE NAMES

USE OF TRADE NAMES OR MANUFACTURERS IN THIS REPORT DOES
NOT CONSTITUTE AN OFFICIAL ENDORSEMENT OR APPROVAL OF THE
USE OF SUCH COMMERCIAL HARDWARE OR SOFTWARE.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER RH-80-2	2. GOVT ACCESSION NO. AD-A085871	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A Simple Method for Treating Diffractive Propagation from a Laser with Diagnostic Optics.		5. TYPE OF REPORT & PERIOD COVERED Technical Report
6. AUTHOR(s) R. W. Jones J. C. Nixon J. F. Perkins		7. PERFORMING ORG. REPORT NUMBER
8. PERFORMING ORGANIZATION NAME AND ADDRESS Commander US Army Missile Command ATTN: DRSMI-RH Redstone Arsenal, Alabama 35809		9. CONTRACT OR GRANT NUMBER(s)
10. CONTROLLING OFFICE NAME AND ADDRESS Commander US Army Missile Command ATTN: DRSMI-RPT Redstone Arsenal, Alabama 35809		11. REPORT DATE 19 November 1979
12. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 10
(12) (13)		14. SECURITY CLASS. (of this report) UNCLASSIFIED
15. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
(14) DRSMI/RH-80-2		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Mode-formative properties Lateral Intensity Distribution Spherical Mirrors Image Plane Propagation Distance Laser		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The diffractive propagation of a complex laser beam through a multi-element optical system is considered. It is shown that the problem can be easily reduced to propagation of a quasi-collimated laser beam in free space through a distance d_{eff} determined by successive applications of a simple lens equation. $d_{sub} \approx d_{eff}$ 395292 Lm		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

0100 0

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

In studying mode-formative properties of lasers and in other connections we have had occasion to manipulate the output of a laser by spherical mirrors or other optical elements prior to observation of an intensity distribution. Provided there is no further aperturing of the beam beyond the laser output, the propagation can be described by a Fresnel integral with an appropriate value of effective propagation distance in free space. To our knowledge, no physically transparent method for determining the value of this propagation distance has been presented for the general case, though Collins' ray-optics diffraction scheme [1] encompasses it provided one works through all the matrix manipulations in detail, and a transformation by Sziklas and Siegman [2,3] can be rather readily applied to the special case of one lens and an observation point preceding its focal point. We refer explicitly only to lenses, but with the understanding that the equivalent mirrors are considered to be included. The paraxial approximation is assumed to hold everywhere.

From physical plausibility arguments one could expect to determine the effective propagation distance by removing one lens at a time, starting with the last one, and moving from the observation (or image) plane to its conjugate (object) plane. While this prescription has physical appeal, its justification requires more than the plausibility argument which mixes a concept (imaging) normally used in connection with incoherent radiation with a concept (diffraction) which is meaningful only for coherent radiation. A detailed justification of the prescription will be given in the following paragraphs. The scheme has also been experimentally confirmed, as will be discussed.

For definiteness, the scheme is depicted in Figure 1 (a) for the particularly simple case of a single lens inserted into the collimated output beam of a laser some distance downbeam from the output. The plane at which the lateral intensity distribution is to be observed is labeled I (following the notion of the image location). For the present discussion we ignore portions of the figure to the right of the image plane. The location of the plane labeled O is determined by the Gaussian lens formula

$$1/d_0 + 1/d_I = 1/f \quad (1)$$

The prescription then is that d_{eff} is simply the distance from the source to the plane O, as illustrated. In this case we assume d_{eff} to be the same as if it were in front of the source, i.e.,

Section <input checked="" type="checkbox"/>	
Section <input type="checkbox"/>	
Section <input type="checkbox"/>	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	

$$d_{\text{eff}} = d_1 - d_0 \quad (2)$$

Note that 0 may be behind the source, i.e., d_{eff} may be negative; this is equivalent to a problem with positive d_{eff} but with an inverted phase distribution at the source aperture. The effective propagation distance d_{eff} can be used in conjunction with the output aperture halfwidth, a , and the wavelength, λ , to form an effective Fresnel number

$$F_{\text{eff}} = a^2 / \lambda d_{\text{eff}} \quad (3)$$

The smaller the value of F_{eff} , the nearer the problem has approached the Fraunhofer limit, in which the observed intensity is the absolute square of the Fourier transform of the complex wave amplitude of the laser output. F_{eff} is closely related to the collimated beam Fresnel number which has been defined by Siegman [2] in connection with unstable resonators. Propagation of a collimated output wave from the laser through a distance d_{eff} would result in an intensity distribution which, except for a transverse scaling factor, is the same as the actual observed distribution.

We follow the notation of Siegman [4] (slightly different from that of Collins) in defining the ABCD matrix of paraxial optics such that the position r and slope r' of a ray after passing through an optical system is given in terms of the position r_0 and slope r'_0 of the corresponding input ray by the matrix relation

$$\begin{pmatrix} r \\ r' \end{pmatrix} = \begin{pmatrix} A & B \\ C & D \end{pmatrix} \begin{pmatrix} r_0 \\ r'_0 \end{pmatrix} \quad (4)$$

The overall ABCD matrix of the optical system is, of course, the matrix product, in reverse order of the ABCD matrices for the various individual components of the system. For simplicity of discussion, the Collins [1] diffraction integral in one transverse dimension can be written in the same form as given in a paper by Siegman [4].

$$E(x) = \left(\frac{1}{B\lambda} \right)^{1/2} \int_{-\infty}^{\infty} \tilde{E}_0(x_0) \exp \left\{ -\frac{j\pi}{B\lambda} (Ax_0^2 - 2xx_0 + Dx^2) \right\} dx_0. \quad (5)$$

Here $E_0(x_0)$ and $E(x)$ are the complex input and output wave amplitudes, and a factor of unit modulus has been suppressed. The effective propagation distance is simple B/A , as can be readily seen by comparison of the previous equation with the form of a conventional Fresnel integral.

To justify the above prescription, first consider the given overall optical system with the final lens removed, using an observation plane which is the conjugate of the final observation plane with respect to the final lens. The effective propagation distance for the reduced (one lens removed) system is taken to be B/A , and we seek to determine the effective propagation distance B''/A'' of the overall system. The overall transfer matrix M'' will be given by $M'M$, where M is the ABCD matrix of the reduced system, and M' is the matrix describing propagation by a distance d_0 to the final lens, the effect of the final lens, and further propagation by a distance d_1 to the final observation plane. For brevity the steps involved in the derivation are outlined. Because of the conjugate relationship of the two observation planes it follows that $B' = 0$. This in turn establishes that

$$A'' = A' A, \quad (6)$$

$$B'' = A' B. \quad (7)$$

Now by division, one readily obtains that the effective propagation distance B''/A'' of the overall system is simply B/A , which is of course the propagation distance for the reduced system as referred to previously. It can also be shown that the lateral magnification is what one would expect on physical plausibility grounds, i.e., $-d_1/d_0$.

The test configuration for measurement of Fresnel/Fraunhofer patterns is shown in Figure 1. A helium neon laser with spatial filter is used as a clean, coherent source of diverging spherical waves of light. An achromatic lens, corrected for spherical aberration is positioned to provide a collimated beam. In Figure 1 (c), a small rectangular aperture (0.635 cm x 1.27 cm) masking most of the beam is placed immediately behind the lens. This apertured, planar wavefront beam propagates a distance d_{eff} , the Fresnel pattern in this plane being magnified and imaged upon a camera film plane by a lens of short focal length.

The intensity distributions of Figure 1(c) are directly correlated (except for magnification or inversion) with the

patterns of Figures 1(a) and 1(b) with a 74.37-cm focal length telescopic objective lens in place. The objective lens is placed approximately 4400 cm from the rectangular aperture in Figure 1(a) and against the aperture in Figure 1(b). The intensity distributions are obtained at an arbitrary distance d_I behind the telescopic objective lens. The image of this intensity distribution is magnified by a short focal length lens and imaged on a camera film plane.

Using the Gaussian lens formula one would expect the pattern of Figure 1(c) to be related to those of Figures 1(a) and 1(b) by the following equation:


$$d_{\text{eff}} = \left| d_I - (d_{If}/d_I - f) \right| . \quad (8)$$

A verification that the Fresnel pattern obtained in Figure 1(c) is analogous to a Fresnel pattern in Figures 1(a) and 1(b) is shown in the following photographs. Figure 2(a) was taken a distance of 4376 cm from the rectangular aperture of Figure 1(c). Accordingly, an image plane d_I of 75.007 cm was chosen in Figure 1(a) to give an object plane a distance 8752 cm to the left of the telescopic objective lens ($d_0 - d_I = 4376$ cm). This intensity distribution is shown in Figure 2(b). The intensity distribution is essentially identical to that of Figure 2(a) which one would expect for a plane wave incident on an aperture.


Another experimental verification was obtained with the rectangular aperture against the lens as in Figure 1(b). In this case, image planes both inside and outside of focus may be chosen to be equivalent to an image plane in Figure 1(c). Figure 3(a) is a Fresnel pattern obtained with d_{eff} being 93 cm from the rectangular aperture of Figure 1(c). An image plane in Figure 2(c) of 371.37 cm ($d_0 = 93$ cm) is shown in Figure 3(b). This is equivalent to an image plane of $d_I = 41.3$ cm inside of focus ($d_0 = -93$ cm) shown in Figure 3(c).

The conclusion obtained from these and other photographs indicates the validity of using the Gaussian lens formula to relate free space propagation of a laser beam to that obtained in an imaging system. In the case described previously, a plane parallel wavefront was vignetted by a rectangular aperture and allowed to propagate a given distance. In practice, any wavefront, e.g., the complex beam from an unstable resonator, can be treated in the


same manner provided the imaging system is of sufficient size to intercept the bulk of all spatially diffracted components of light.



(a)




(b)




(c)

Figure 1. Experimental configurations for determining equivalency of Fresnel/Fraunhofer distributions.




(a)




(b)

Figure 2. Diffractive propagation of a rectangular laser beam over an effective distance, d_{eff} , of 4376 cm.



(a)



(b)



(c)

Figure 3. Diffractive propagation of a rectangular laser beam over an effective distance, d_{eff} , of 93 cm.

REFERENCES

1. S. A. Collins, Jr., Journal of the Optic Society of America, 60, 1168 (1970).
2. E. A. Sziklas and A. E. Siegman, Applied Optics, 14, 1874 (1975).
3. E. A. Sziklas and A. E. Siegman, Proceedings of the IEEE, 62, 410 (1974).
4. A. E. Siegman, IEEE Journal of Quantum Electronics, QE-12, 35 (1976).

DISTRIBUTION

	No. of Copies
Defense Technical Information Center Cameron Station Alexandria, Virginia 22314	12
US Army Materiel Systems Analysis Activity ATTN: DRXSY-MP Aberdeen Proving Ground, Maryland 21005	1
IIT Research Institute ATTN: GACIAC 10 West 35th Street Chicago, Illinois 60616	1
DRSMI-LP, Mr. Voigt	1
-R, Dr. Kobler	1
-RPR	3
-RPT (Reference Copy)	1
-RPT (Record Copy)	1
-RHS, Mr. Jones	15

